

6U860A

- 6U GPU server barebone
- Supports 5 CRPS module
- NVMe backplane
- 6 12038 hot-swappable fans
- 4 8038 fans



Product parameters

|                        |                                                                                   |
|------------------------|-----------------------------------------------------------------------------------|
| Chassis style          | Rack                                                                              |
| Structure              | 6U                                                                                |
| Dimension              | D860*W447*H265MM (482MM width with mounting ears)                                 |
| Material               | SGCC1.0MM                                                                         |
| Cooling Fan            | 6 12038 hot-swappable fans, 4 8038 fans, Supports intelligent temperature control |
| Compatible Motherboard | HPTX(15"*13")/EATX(12"*13")/CEB(12"*10.5")/ATX(12"*9.6")                          |
| HDD Backplane          | NVMe backplane, compatible with U.2/SATA HDD/SSD                                  |
| HDD Bay                | 4 2.5" hot-swappable HDD/SSD bays                                                 |
| Power supply Support   | Supports 5 CRPS module, supports N + N redundancy /N + 1 redundancy               |
| GPU slot               | Supports 8 GPUs, GPU maximum length limit: 360MM                                  |
| GPU Riser              | 10 Gen4 GPU risers and accompanying cables                                        |
| Slide Rail             | Optional                                                                          |
| Packaging Details      | Carton Box with PE foam and polybag                                               |
| Package Size           | D1060*W580*H380MM                                                                 |
| Single gross weight    | 35KG                                                                              |

