

6U860C

- 6U Rackmount Server Chassis
- NVMe direct-connect backplane
- Supports 4+1 redundant power supplies
- 6pcs 12038 hot-swap fans



Product parameters

| | |
|------------------------------|---|
| Chassis style | Rack-mounted |
| Structure | 6U |
| Dimension | L860*W447*H265MM (including the width of the ears is 482MM) |
| Material | SGCC1.0MM |
| Cooling Fan | Supports intelligent-temperature control, 6pcs 12038 hot-swap fans, 4pcs 8038 hot-swap fans |
| Compatible Motherboard | ROME2D32GM-2T and GENOA2D24G-2L+ motherboards |
| Compatible power supply | 4+1 redundant power supplies |
| HDD Bay | 4*2.5"hot-swap drive bays |
| Applicable hard drive | Compatible with U.2, SAS and SATA hard drives |
| HDD Backplane | NVMe direct-connect backplane, Supports GPIO |
| Graphics card slot | Support 8 Gaming graphics cards, and the maximum length limit of the graphics card is 360MM |
| Graphics card extender cable | PCIe5.0 adapter backplane*8, PCIe4.0 adapter backplane*2, MCIO to MCIO cable*20 |
| power supply cable | Redundant power supply board *1, power supply cable *17 |
| Slide Rail | Optional |
| Packaging Details | Carton Box with PE foam and polybag |
| Package Size | L1060*W580*H380MM |
| Single gross weight | 30KG |

